



CLEAR ZONE WITH 1:4 DITCH SLOPES
 PER TABLE 3.1
 2002 AASHTO ROADSIDE DESIGN GUIDE
 100 km/h (62 mph DESIGN SPEED)

* ASSUMES SEASONAL HIGH WATER IS APPROXIMATELY
 0.5' BELOW EXISTING GROUND AND 1' OF ROADWAY BASE
 CLEARANCE IS REQUIRED BASED ON TABLE 2.6.3 OF PPM
 VOL. 1 FOR URBAN FACILITY.

** ADJUST RIGHT-OF-WAY WIDTH AS NEEDED (NOT
 TO EXCEED 250') IN ORDER TO PLACE COMBINATION
 BICYCLE-PEDESTRIAN PATH & FORESLOPE WITHIN
 RIGHT-OF-WAY

YEAR 2012 & YEAR 2037
4-LANE TYPICAL SECTION
CR 2209
CR 210 TO CR 208 (2012)
SR 16 TO CR 208 (2037)

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

RS&H
 Reynolds, Smith and Hills, Inc.
 10748 Deerwood Park Boulevard South
 Jacksonville, Florida 32256-0587
 904-295-2000
 FL Cert. No. EB0006820
 Engineer of Record: Daniel Kratoch, Jr., P.E. No. 30378

ST. JOHNS COUNTY
ENGINEERING DIVISION
2740 INDUSTRY CENTER ROAD
ST. AUGUSTINE, FL 32084

FIGURE 7.4.3
4-LANE SECTION

SHEET NO.
