



CRITERIA

- 1) DESIGN SPEED = 55 mph
- 2) MIN. RECOVERABLE TERRAIN = 30' PER FDOT STANDARD 700
- 3) 3' SUBBASE CLEARANCE REQUIRED ABOVE SEASONAL HIGH WATER (PPM TABLE 2.6.3)
- 4) SEASONAL HIGH WATER = APPROX. 1' BELOW EXISTING GROUND

NOTES:

- 5) SCENIC BUFFER WHERE REQUIRED.
- 6) MULTI-USE PATH MAY BE LOCATED WITHIN 75' SCENIC BUFFER WHERE PROVIDED.

**CR 2209
CR 208 TO MIDWAY BETWEEN IGP AND SR 16**

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

RSH
 Reynolds, Smith and Hills, Inc.
 10748 Deerwood Park Boulevard South
 Jacksonville, Florida 32256-0587
 904-295-7000
 FL Cert. No. EB0006820
 Engineer of Record: Daniel Kratoch, Jr., P.E. No. 30378

**ST. JOHNS COUNTY
ENGINEERING DIVISION
2740 INDUSTRY CENTER ROAD
ST. AUGUSTINE, FL 32084**

**FIGURE 8.2.1
4-LANE TYPICAL SECTION
CR 208 TO MIDWAY BETWEEN
IGP AND SR 16**

SHEET NO.
