



CRITERIA:

- 1) DESIGN SPEED = 55 mph
- 2) MIN. RECOVERABLE TERRAIN = 30' PER FDOT STANDARD 700
- 3) 3' SUBBASE CLEARANCE REQUIRED ABOVE SEASONAL HIGH WATER (PPM TABLE 2.6.3)
- 4) SEASONAL HIGH WATER = APPROX. 1' BELOW EXISTING GROUND

NOTES:

- 5) RIGHT-OF-WAY WIDTH IS 200' WHERE A 75' SCENIC BUFFER IS PROPOSED ON EACH SIDE.
- 6) MULTI-USE PATH IS LOCATED WITHIN 75' SCENIC BUFFER WHERE PROVIDED.

**CR 2209
MIDWAY BETWEEN IGP AND SR 16 TO CR 210**

		REVISIONS			
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

RS&H
Reynolds, Smith and Hills, Inc.
10748 Deerwood Park Boulevard South
Jacksonville, Florida 32256-0587
904-295-2000
FL Cert. No. EB0006620
Engineer of Record: Daniel Kratoch, Jr., P.E. No. 30378

**ST. JOHNS COUNTY
ENGINEERING DIVISION
2740 INDUSTRY CENTER ROAD
ST. AUGUSTINE, FL 32084**

**FIGURE 8.2.2
6-LANE TYPICAL SECTION
MIDWAY BETWEEN IGP &
SR 16 TO CR 210**

SHEET NO.